

Ŋ Π 1'-0"

- HARDWARE TO HAVE BRUSHED CHROME FINISH, PUSH BAR AND 'SCHLAGE' KEYED LEVER ON INSIDE & OUTSIDE OF ROOM, DEAD BOLT KEYED TO OWNER'S KEY. LCN 4041H HOLD OPEN DOOR CLOSER: 180 DEG., 5LB.

 WELDED FLUSH DOOR FRAME TO BE 16 GA, STEEL, COLOR TO MATCH EXISTING FRAME, NO DOOR SILL, FRAME TO BE WELDED WHEN ADJACENT TO STEEL AND BRACED & SECURELY FASTENED AT OTHER LOCATIONS, AS APPROVED BY PROJECT ENGINEER.

 LEFT HAND DOOR TO BE 18 GA, STEEL WITH 1/4" CLASS 2 TEMPERED GLASS, THREE BALL STEEL WITH AN OIL BASE TINTED TO MATCH EXISTING.

 PRIME ALL STEEL WITH AN OIL BASE TINTED TO MATCH PAINT, APPLY 2 COATS OF AN OIL BASE FINISH PAINT WITH COLOR AND LUSTER TO MATCH EXISTING.

- REUSE EXISTING CARPET TILE FROM UNDER RAMP OR THOSE PROVIDED BY OWNER AND SUPPLY ALL PREPARATION AND INSTALLATION MATERIALS.

 RAMP IS TO BE PREFABRICATED OUT OF SOILD WOOD FRAMING WITH 3/4" AC PLYWOOD, FRAMING SUPORTS NOT TO EXCEED 12" D.C.

 SUBMIT SHOP DRAWING FOR PROJECT ENGINEER APPROVAL BEFORE STARTING WITH ANY SHOP FABRICATING, SOME VARIATIONS ON DIMENSIONS AND DESIGN MAY BE ACCEPTABLE TO COMPLY WITH STANDARD STOCK SIZES.

 RAIL MUST BE OF SUFFICIENT GAUGE AND SECURED TO MEET THE 50# LATERAL THRUST REQUIREMENT, IT WILL ALSO MEET A.D.A. CODE AND BE FINISHED AS OTHER STEEL. WALL MOUNTED RAIL TO SPAN RAMP DNLY, NOT LANDING.

 CONTRACTOR MUST INFORM PROJECT ENGINEER OF ANY WIRING OR MISC.

 ITEMS THAT MAY INTERFERE WITH DOOR INSTALLATION BEFORE PROCEEDING WITH WORK, ANY EXISTING WIRES OR CONDUIT MUST BE LEFT IN PLACE AND WORKED AROUND, SUSTAINED NOISE OVER 75 DB, MUST BE PERFORMED FROM 3AM-6AM ANY DAY OF THE WEEK, MUST PROVIDE 48 HOURS NOTICE TO PROJECT ENGINEER BEGINNING SUCH WORK.


 WORK AREA MUST BE SEALED OFF FROM OPERATIONS ROOM TO PREVENT SPREAD OFF DUST, ODOR, AND/OR EXCESSIVE NOISE.

RAMING

1'-0"

Sheet

0



EXIST, CONC. FLOOR EXISTING RAISED - FLOOR BOLT RAILING TO BELOW RAISED FL APPROX. 10" 2'-10 CONC. FLOOR 4" -20" -|10" 1/2" $\parallel \parallel$ 1/4" CLASS 2 TEMPERED GLASS WELDED FLUSH FRAME TO MATCH DOOR AND EXISTING FRAMES 1'-0" 3/4" AC PLYWD. CARPET TILE ---- \mathcal{D} PUSH BAR THIS SIDE @ 32 1/2" HT. SECURE RAILING TO RAMP FRAMING W/ 'C' CLAMP (TYP.) COVER EXPOSED FACE OF RAMP WITH CARPET TO MATCH EXIST. 41 ω_{ω}^{ω} LEVER OPENER BOTH SIDES

CENTER - DOOR INSTALL BUILDING MARTIN LUTHER KING, JR. BLVD MADISON, WISCONSIN

PUBLIC DEPARTMENT WORKS COUNTY WISCONSIN DANE

